

Grandstand Attractions Inc.

2022 Bone Stock Rules

New Rules are in Red

Participants Regulations: Bone stock class is open to all men and women 15 and over, if under the age of 18 you must have a notarized permit signed by a parent/guardian.

Driver may move forward or backward. Driver must make contact every 60 seconds or be disqualified. No sandbagging, if you sandbag the race will be stopped and a sandbagger flag will be put on top of your car. You must show visible damage or must move when hit.

Prize Money: Is different for every show. Check schedule for this.

Preparation of cars: This class will be limited to **1980 & newer**. All glass, chrome, pot metal, carpet, head lights, taillights, back seats. Anything flammable must be removed before reaching exhibit area. Mandatory: must have number on both front doors and on roof must, be big enough and bright enough to read. Use your choice of number No profanity.

THE RULES BELOW ARE THE ABSOLUTE MAX YOU MAY DO TO A CAR.

1. Dash may be removed.
2. Stock gas tank can be used under car. If, changed to inside it must be a metal fuel cell no exceptions. Must be secured properly and no fuel leakage. No more than 6 gallons gas. (gas tanks like in crown vics should be removed)
3. Battery may be relocated to inside of car but must be secured properly (1 automotive battery)
4. **HOOD-You may use 2 all thread no larger than 5/8" with washers no bigger than 6 inches outside diameter. All thread may go through the frame. (THESE 2 MUST BE ON THE OUTSIDE OF RADIATOR SUPPORT).**
5. Hood must have a 5x5 hole cut in it to extinguish fires. Hood must open for inspection and must remain on hinges. You can use 8 pieces of chain 3/8 6 in hood to fender, 2 from hood to bumper. or you can use 9 wire the same way with 3 wraps per fastening spot. Must have windshield bar from top of windshield to top of fire wall you can use 9 wire, chain, or 3-inch flat metal. 2 max in this area.
6. Trunks must be on hinges. You can use 8 pieces of chain 3/8 in trunk 6 to fasten trunk lid and 2 from trunk lid to bumper. Or you can use 9 wire the same way with 3 wraps per fastening spot **or six 3/8" bolts - no longer than 3"**. You can tuck 50% of trunk lid only or remove trunk lid completely.
7. **BUMPERS** may have a 4"x 5"x1/4" plate welded or bolted for mounting purposes. This plate may bolt to frame with 4 bolts **or welded to frame with one pass 1/2" wide MAX (If welded to frame, shocks must be removed)**. As stated in rule 4 & 5 you can also use nine wire or chain along with bolting. You may swap out aluminum bumpers to 80's and newer steel bumper or a **single piece of 4"x4" tubing, 3/16" thick—tubing must be straight and no wider than inside of front tires and must attach the same as stock.**
8. Doors you can use 6 pieces of chain 3/8 per door or 6 pieces of 9 wire per door with 3 wraps. Both front doors you can have a six-inch-wide piece of channel or equivalent from 6 inches in front of front doors to 6 inches behind front doors. May be welded or bolted. May have four bar floating cage. not to exceed 6-inch cage material, cannot go any further back than 6 inches of front doors. front bar must be in dash area, must be at least 5 inches off floor.
9. TIRES: D.O.T. approved light truck tires max.
10. NO HEADER PIPES.
11. REAR ENDS: Locking of rear ends permitted.
12. FRAME Notching of frame permitted but cannot be welded back together.
13. Push pull shifter allowed.
14. Push button start allowed.
15. THIS IS THE MAX OF WHAT YOU CAN DO ON A BONE STOCK CAR. DO NOT DO ANYMORE THAN THIS OR YOU WON'T BE RUNNING THIS CLASS.

WEBSITE: WWW.GSADEMODERBY.COM

EMAIL: gsacrashqueen@aol.com PHONE OR TEXT: (217) 306-4025